

UT320 SERIES

Mini Contact Type Thermometers

UT320A and UT320D are single and dual channel contact type thermometers respectively. These highly accurate thermometers have a wide temperature range. UT320D can also calculate the temperature difference of its two channels. UT320 can be used with any K or J temperature probe.

- Auto power off
- Low battery indication
- Data hold
- °C/°F selection

- MAX/MIN/AVG
- Mode selection (K/J)
- Backlight
- 1m drop proof







UT320D

| | Range | UT320A | UT320D |
|--------------------------------|---|-----------|-----------|
| Certificates | CE, RoHS | | |
| Temperature measurement (K) | -50°C~1300°C | ±(0.5%+1) | ±(0.5%+1) |
| Temperature measurement (J) | -50°C~1200°C | ±(0.5%+1) | ±(0.5%+1) |
| Display mode | | Single | Dual |
| Difference measurement (T1-T2) | | | ٧ |
| Operating temperature | 0°C~40°C | | |
| Operating humidity | ≤80%RH | | |
| Power | 1.5V battery (R03) x 3 | | |
| Display | 37.4mm x 36.4mm | | |
| Product net weight | 60g | | |
| Product size | 120mm x 53mm x 28mm | | |
| Standard accessories | K-type temperature probe, batteries, English manual | | |
| Standard individual packing | Gift box | | |
| Standard quantity per carton | 20pcs | | |
| Standard carton measurement | 332mm x 225mm x 200mm | | |
| Standard carton gross weight | 3.4kg | | |